

EBERSOL BALE ELEVATOR

Construction Features:

- . galvanized sheet metal
- . V-belt drive with #55 chain reduction
- . flared sides and hopper
- . pre-lubricated self-aligning bearings

Operating Features:

- . top drive pulls load rather than pushing it
- . heavy-duty undercarriage allows easy transportation and height adjustment
- . handles bales, grain, corn cobs, ensilage, etc.
- . corn screen optional

SPECIFICATION CHART

| | | Approx. | | | | |
|-------|--------|---------|------|-----------|----------|-----------------------------------|
| Model | Length | Height | Axle | Weight | Motor | Miscellaneous all sizes |
| 16' | 18' | 13' | 6' | 670 lbs. | 1/2 hp | trough width at bottom - 20" |
| 24' | 26' | 21' | 6' | 935 lbs. | 3/4 hp | trough width at top - 27" |
| 28' | 30' | 23' | 7' | 1090 lbs. | 1 hp | depth of straight trough - 4-1/2" |
| 32' | 34' | 25' | 7' | 1195 lbs. | 1 hp | depth of flared trough - 6" |
| 36' | 38' | 28' | 7' | 1352 lbs. | 1-1/2 hp | total depth of trough - 10-1/2" |
| 40' | 42' | 29' | 7' | 1510 lbs. | 1-1/2 hp | flight spacing - 2'/4'/6' |
| 48' | 50' | 38' | 8' | 1840 lbs | 2 hp | (4' standard) |



Manufactured by:

BAUMAN
MANUFACTURING LIMITED

Original Equipment Manufacturer

Tel (519) 669-4333 Fax (519) 669-2431

Distributed by: